

Thermic 6,5

T.V. Thermal Valve



Equipped with:

- Three ceramic coated pistons, brass linear pump head with built-in by-pass valve.
- Suction and delivery S/S valves.
- 6.5 HP unleaded gasoline engine.
- Integrated detergent suction with external suction probe.
- Glycerine pressure gauge.
- Hose-reel **(optional)**.
- Suction hose with check valve **(optional)**.
- Steel frame.
- Hose holder.
- Nozzles holder.
- 3,1 l gasoline tank.

STANDARD EQUIPMENT

- 6.001.0082 Gun M22 - 1/4"



- 6.002.0322 Lance M22 with nozzle-holder.



- 5.012.0477 High pressure nozzle set



- 4.618.0166 High pressure hose 10 m



Optional:

- 6.608.0007 High-pressure hose-reel (hose not included)
- Suction hose with check valve 5.012.0319



| | Thermic 6,5 |
|-------------------------|-------------------------------|
| code | 8.601.0175C |
| operat. pressure max | 180 bar - 2610 psi |
| delivery rate | 690 l/h - 2.77 GPM |
| engine type/hp | Lavor/6,5 |
| pump type/RPM | MP4/3400-3600 RPM |
| max. temp. inlet/outlet | 40 °C |
| dimension/weight | 47x57x57cm/38,5 Kg - 84.9 lbs |