

**Torrens**

**STANDARD EQUIPMENT**



- 3.700.0036 Gun M22 - 3/8" with rotating coupling



- 3.701.0015 Lance M22 high pressure



- 3.103.0050 Nozzle type 045 (mod. 1211/2015)
- 3.103.0052 Nozzle type 055 (mod. 1515)



- 4.618.0012 High pressure hose 10 m



- Power cable 5 m

Optional:

- 3.697.0044 Antiscale LC-PRECAL (pcs. 4 x 5 lt.)

- ROTOX lance code:  
6.602.0040 - (mod. 2015/1211)  
6.602.0041 - (mod. 1515)

**Equipped with:**

- 4 poles electrical motor (1450 RPM) with thermal protection with built-in by-pass valve
- Suction and delivery S/S valve
- Total stop
- Power cable (m 5)
- Auxiliary motor for burner air-cooling and two ways fuel pump
- Temperature regulation gauge
- Glycerine pressure gauge
- Vertical burner with high thermal efficiency steel coil

	Torrens 1211 LP	Torrens 1515 LP	Torrens 2015 LP
code	8.627.0001C	8.627.0002C	8.627.0003C
operat. pressure	110 bar	150 bar	200 bar
delivery rate	660 l/h	900 l/h	900 l/h
abs. power/voltage	3000 - 230V~50Hz	5500 - 400V~50Hz 3 ph	7300 - 400V~50Hz
motorpump type/RPM	MP4/1450 RPM	CL4/1450 RPM	CL4/1450 RPM
max. water inlet/outlet temp.	40/110 °C	40/110 °C	40/110 °C
dimension/weight	120x74x101cm/140 Kg	120x74x101cm/158,5 Kg	120x74x101cm/144,5 Kg